

Cambridge International AS & A Level

PHYSICS**9702/53**

Paper 5 Planning, Analysis and Evaluation

May/June 2026**MARK SCHEME**Maximum Mark: 30

Published

This mark scheme contains the instructions and marking guidance that our examiners used to mark candidate responses for this component.

Before they start marking, examiners complete a standardisation process. They review a range of candidate responses and discuss the mark scheme in detail to agree which answers can and cannot be accepted. Examiners award marks where it is clear that candidate responses have met the requirements of the mark scheme. These requirements may vary between different components or different versions of the same component, depending on the exact requirements of the question and the candidate responses seen during the standardisation process.

Sometimes, our mark schemes may allow marks to be awarded to responses which contain elements that are factually incorrect or for content not covered by the syllabus. We do this in response to the demands of a specific question to support candidates and make sure that our assessments are fair. However, these allowances should not be used as a guide for teaching and learning.

We cannot discuss the mark scheme with schools, and we recommend that schools read the mark scheme together with the assessment material and the Principal Examiner Report for Teachers.

This document consists of **14** printed pages.

General marking principles

All examiners must apply these marking principles when marking candidate responses.

1	Examiners must award marks for each response in line with: - the specific content defined in the mark scheme - the specific skills defined in the mark scheme or in the level descriptions - the standard of response required as exemplified by the standardisation scripts.
2	Examiners must award whole marks (not half marks, or other fractions).
3	Examiners must award marks positively . This means that: - marks are not deducted for errors or omissions - marks are awarded for correct/valid answers as defined in the mark scheme and also for other valid answers which go beyond the scope of the syllabus and mark scheme referring to your team leader as appropriate - the quality of spelling, punctuation and grammar are judged only when the mark scheme indicates that these features are specifically assessed in the question. However, the meaning of all responses must be unambiguous.
4	Examiners must consistently apply the requirements of the mark scheme and any rules for what to do when candidates have not followed instructions correctly.
5	Examiners must use the full range of marks defined in the mark scheme, unless limited by the quality of the candidate responses seen.
6	Examiners must award marks according to the mark scheme and must not award marks with grade thresholds or grade descriptions in mind.

Science-Specific Marking Principles

1	Examiners should consider the context and scientific use of any keywords when awarding marks. Although keywords may be present, marks should not be awarded if the keywords are used incorrectly.
2	The examiner should not choose between contradictory statements given in the same question part, and credit should not be awarded for any correct statement that is contradicted within the same question part. Wrong science that is irrelevant to the question should be ignored.
3	Although spellings do not have to be correct, spellings of syllabus terms must allow for clear and unambiguous separation from other syllabus terms with which they may be confused (e.g. ethane / ethene, glucagon / glycogen, refraction / reflection).
4	The error carried forward (ecf) principle should be applied, where appropriate. If an incorrect answer is subsequently used in a scientifically correct way, the candidate should be awarded these subsequent marking points. Further guidance will be included in the mark scheme where necessary and any exceptions to this general principle will be noted.
5	<u>'List rule' guidance</u> For questions that require <i>n</i> responses (e.g. State two reasons ...): • The response should be read as continuous prose, even when numbered answer spaces are provided. • Any response marked <i>ignore</i> in the mark scheme should not count towards <i>n</i>. • Incorrect responses should not be awarded credit but will still count towards <i>n</i>. • Read the entire response to check for any responses that contradict those that would otherwise be credited. Credit should not be awarded for any responses that are contradicted within the rest of the response. Where two responses contradict one another, this should be treated as a single incorrect response. • Non-contradictory responses after the first <i>n</i> responses may be ignored even if they include incorrect science.

6 Calculation specific guidance

Correct answers to calculations should be given full credit even if there is no working or incorrect working, **unless** the question states 'show your working'.

For questions in which the number of significant figures required is not stated, credit should be awarded for correct answers when rounded by the examiner to the number of significant figures given in the mark scheme. This may not apply to measured values.

For answers given in standard form (e.g. $a \times 10^n$) in which the convention of restricting the value of the coefficient (a) to a value between 1 and 10 is not followed, credit may still be awarded if the answer can be converted to the answer given in the mark scheme.

Unless a separate mark is given for a unit, a missing or incorrect unit will normally mean that the final calculation mark is not awarded. Exceptions to this general principle will be noted in the mark scheme.

7 Guidance for chemical equations

Multiples / fractions of coefficients used in chemical equations are acceptable unless stated otherwise in the mark scheme.

State symbols given in an equation should be ignored unless asked for in the question or stated otherwise in the mark scheme.

Annotations guidance for centres

Examiners use a system of annotations as a shorthand for communicating their marking decisions to one another. Examiners are trained during the standardisation process on how and when to use annotations. The purpose of annotations is to inform the standardisation and monitoring processes and guide the supervising examiners when they are checking the work of examiners within their team. The meaning of annotations and how they are used is specific to each component and is understood by all examiners who mark the component.

We publish annotations in our mark schemes to help centres understand the annotations they may see on copies of scripts. Note that there may not be a direct correlation between the number of annotations on a script and the mark awarded. Similarly, the use of an annotation may not be an indication of the quality of the response.

The annotations listed below were available to examiners marking this component in this series.

Annotations

Annotation	Meaning
	benefit of the doubt given
	correct awarding one mark from additional detail 1. similar numbered ticks are used for additional detail 2, 3, 4 etc.
	correct point or mark awarded
	defining the problem mark
	error carried forward applied
	error in number of significant figures
	incorrect or insufficient point ignored while marking the rest of the response
	incorrect point or mark not awarded
	incorrect unit
	information missing or insufficient for credit

Annotation	Meaning
MO	methods of data collection mark
SEEN	point has been noted, but no credit has been given or blank page seen
REP	repetition in response

Abbreviations

ECF	error carried forward
SF	significant figures
POT	power of ten

PUBLISHED

Question	Answer	Marks	Guidance
1	Defining the problem		Annotate with P.
	Vary a and measure T / period (of oscillations) or a is the independent variable and T / period (of oscillations) is the dependent variable	1	This mark could be awarded having read the candidate's script all the way through. Allow t Allow time for period Not a or T constant
	Keep L <u>constant</u>	1	Allow same for constant
	Methods of data collection		Annotate with M0
	Labelled diagram of workable experiment including: - rod fixed to stand(s) - bar suspended by strings - stand(s) on a bench - two labels from bench, a, L, string, bar, rod, stand / boss / clamp, centre of bar.	1	Allow fixed to a ceiling Ignore rule
	Measure the time t for n oscillations and $T = t / n$	1	Ignore counting oscillations in a fixed time Note $n \geq 5$ if n specified
	Use a stopwatch to measure $(n)T$ or time for n oscillations	1	Allow period Allow timer for stopwatch Ignore vague reference to time Allow video and detailed use of time stamp for start and end of oscillation
	Use rule(r) to determine a and L	1	Allow calipers Not micrometer

PUBLISHED

Question	Answer	Marks	Guidance
1	Method of Analysis		Annotate with ✓
	Plot a graph of $\lg T$ against $\lg a$ or $\lg T$ against $\lg \frac{1}{a}$ or $\ln T$ against $\ln a$ or equivalent	1	Note drawn axes take priority. Allow log for lg
	$q = -\text{gradient}$ for $\lg T$ against $\lg a$ or $q = \text{gradient}$ for $\lg T$ against $\lg \frac{1}{a}$	1	Note Must be consistent with drawn graph. $q = \frac{1}{\text{gradient}}$ for $\lg a$ against $\lg \frac{1}{T}$
	$P = \frac{1}{2\pi} \sqrt{\frac{M}{L}} \times 10^{y\text{-intercept}}$ for $\lg T$ against $\lg a$ or $\lg T$ against $\lg \frac{1}{a}$ or $P = \frac{1}{2\pi} \sqrt{\frac{M}{L}} \times e^{y\text{-intercept}}$ for $\ln T$ against $\ln a$	1	Note Must be consistent with drawn graph. $P = \frac{1}{2\pi} \sqrt{\frac{M}{L}} \times 10^{q \times y\text{-intercept}}$ for $\lg a$ against $\lg \frac{1}{T}$
	Additional detail including safety considerations	6	Annotate with numbered tick
	D1 Precaution linked to <u>bar / rod falling</u> onto bench, e.g. G-clamp stand(s) to bench to prevent <u>bar / rod falling</u> or cushions / sand tray (on bench / on the surface immediately below bar) to prevent <u>bar / rod falling</u>		Allow heavy weights on stand(s) Ignore cushions / sand tray on floor for use of bench Note position may be confirmed from diagram
	D2 Keep M constant		Allow same for constant
	D3 Method to measure M , e.g. use a (top-pan) balance		Allow scales Ignore scale Allow spring balance Allow newton meter / weight with division by g

PUBLISHED

Question	Answer	Marks	Guidance
1	D4 Description of method to ensure each a is measured from the centre of the bar, e.g. measure length of bar and divide by two and mark midpoint of bar or measure from the end of the bar to each string to ensure each a is the same		Note text mark Allow determine balance point and mark the balance point
	D5 Description of method to keep bar horizontal e.g. use a spirit level or measure L at different positions on the bar / measure height of bar from the bench in different positions to check L / height are the same or description of method to keep the strings vertical, e.g. check with set square against <u>bar</u> or <u>rod</u> and <u>string</u> / measure a to each string at the bar and at the rod to check that they are same / use a plumb line		Note text mark Allow level for horizontal Ignore rod
	D6 Description of method to prevent strings from sliding, e.g. use adhesive putty to prevent the strings from sliding		Allow notches or holes or grooves
	D7 Method to determine accurate values of T , e.g. use small amplitude / angle oscillations or use a fiducial marker <u>at the midpoint of the oscillation</u>		Allow displacement Ignore not (too) large
	D8 Use large values of L <u>to increase</u> T (to reduce percentage uncertainty of T)		Allow t for T
	D9 Repeat determination of T for the same value of a and calculate the average T		Allow t for T Allow each for same

PUBLISHED

Question	Answer	Marks	Guidance
1	D10 Relationship valid <u>if</u> a straight line is produced (with $y\text{-intercept} = \lg\left(2\pi P\sqrt{\frac{L}{M}}\right)$). Do not accept through the origin.		Note Must be consistent with drawn graph. Ignore 'data' / 'graph' / 'experiment' / 'results' / 'correlation' valid.

PUBLISHED

Question	Answer	Marks	Guidance							
2(a)	$\text{gradient} = \frac{18\beta z}{g(\rho - \sigma)}$	1								
2(b)	<table><tr><td>$\frac{1}{d^2} / \text{mm}^{-2}$</td></tr><tr><td>0.15 or 0.148</td></tr><tr><td>0.11 or 0.111</td></tr><tr><td>0.087 or 0.0865</td></tr><tr><td>0.059 or 0.0595</td></tr><tr><td>0.052 or 0.0517</td></tr><tr><td>0.040 or 0.0400</td></tr></table>	$\frac{1}{d^2} / \text{mm}^{-2}$	0.15 or 0.148	0.11 or 0.111	0.087 or 0.0865	0.059 or 0.0595	0.052 or 0.0517	0.040 or 0.0400		
	$\frac{1}{d^2} / \text{mm}^{-2}$									
	0.15 or 0.148									
	0.11 or 0.111									
0.087 or 0.0865										
0.059 or 0.0595										
0.052 or 0.0517										
0.040 or 0.0400										
	Values of $\frac{1}{d^2}$ correct as shown in table above.	1	Allow mixture of sf in $\frac{1}{d^2}$							
	Uncertainties in $\frac{1}{d^2}$ from ± 0.01 to ± 0.002 .	1	Allow more than 1 sf Ignore one minor variation in uncertainties in rows 2–5 Allow uncertainty in row one between ± 0.010 and ± 0.013							
2(c)(i)	Six points from (b) plotted correctly. Must be within half a small square. Diameter of points must be less than half a small square.	1	Check second and fourth plots from the left. Allow ecf from 2(b)							
	Error bars in $\frac{1}{d^2}$ plotted correctly. All error bars to be plotted. Total length of bar must be accurate to less than half a small square and symmetrical.	1	Check second and fourth plots from the left. Allow ecf from 2(b)							

PUBLISHED

Question	Answer	Marks	Guidance
2(c)(ii)	Straight line of best fit drawn. Do not accept line from top point to bottom point. Thickness of the line should be less than half a small square. Line must pass between (0.064, 2.50) and (0.066, 2.50) and between (0.134, 5.50) and (0.138, 5.50)	1	Note no ecf
	Worst acceptable line drawn. Steepest or shallowest possible line that passes through all the error bars. Thickness of the line should be less than half a small square. All error bars must be plotted.	1	Allow ecf from points / error bars plotted incorrectly – examiner judgement. Note wal may be constrained by intermediate error bar.
2(c)(iii)	Gradient determined with clear substitution of data points into $\Delta y / \Delta x$; distance between data points must be greater than half the length of the drawn line.	1	Check the read offs. Work to less than half a small square in each direction. Ignore POT. Expect ≈ 36 to $48 (\times 10^{-6})$ Expect $\Delta x \geq 0.07$
	Gradient determined of worst acceptable line with clear substitution of data points into $\Delta y / \Delta x$. uncertainty = (gradient of line of best fit – gradient of worst acceptable line) or uncertainty = $\frac{1}{2}$ (steepest worst line gradient – shallowest worst line gradient)	1	Method of determining absolute uncertainty. Check read-offs are not used in the bfl gradient unless on wal. Check subtraction.
2(d)	$(6600 \pm 100) (\text{kg m}^{-3})$	1	Ignore missing brackets

PUBLISHED

Question	Answer	Marks	Guidance
2(e)(i)	Value of β determined using gradient and β given to 2 or 3 sf $\beta = \frac{g(\rho - \sigma) \times \text{gradient}}{18z}$	1	Ignore POT Allow ecf from 2(c)(iii) and 2(d) Expect $\approx 1.5 \times 10^n$
	β determined using gradient and β given with SI units with appropriate power of ten Unit of β : $\text{kg m}^{-1} \text{s}^{-1}$	1	Allow ecf from 2(c)(iii) and 2(d) Expect $\approx 1.5 (\text{kg m}^{-1} \text{s}^{-1})$ or $\approx 0.0015 (\text{kg mm}^{-1} \text{s}^{-1})$ or $\approx 1.5 (\text{g mm}^{-1} \text{s}^{-1})$ Allow Pa s or $\text{Nm}^{-2} \text{s}$ Not $\text{kg mm m}^{-2} \text{s}^{-1}$ Allow unit for gradient substituted into correct expression but incorrectly calculated
2(e)(ii)	Percentage uncertainty in β with method shown. $\% \text{uncert} = \left(\frac{\Delta(\rho - \sigma)}{(\rho - \sigma)} + \frac{\Delta \text{gradient}}{\text{gradient}} + \frac{\Delta z}{z} \right) \times 100$ or Max/min methods, e.g. $\max \beta = \frac{g}{18} \times \frac{\max(\rho - \sigma) \times \max \text{gradient}}{\min z}$	1	Allow max / min methods Allow ecf from 2(c)(iii) and 2(d) Note must be greater than 2% (3.5% with correct 2(d))

PUBLISHED

Question	Answer	Marks	Guidance
2(f)	t determined to a minimum of 2 sf from 2(c)(iii) or 2(e) with clear method and use of correct power of ten for d. $t = \text{gradient} \times \frac{1}{(0.012 \text{ (m)})^2}$ or $t = \frac{18\beta z}{g(\rho - \sigma) \times (0.012 \text{ (m)})^2}$	1	Allow ecf from 2(c)(iii), 2(d) and 2(e)(i) Expect $\approx 0.28 \text{ (s)}$ Note $\frac{1}{(0.012 \text{ (m)})^2} = 6944$
	Absolute uncertainty determined with correct substitution. For use of gradient from 2(c)(iii): $\Delta t = \left(\frac{\Delta \text{gradient}}{\text{gradient}} + \frac{2 \times 0.01}{1.20} \right) \times t \text{ or}$ $\Delta t = \left(\frac{\text{max gradient}}{(\text{min } d)^2} \right) - t \text{ or } \Delta t = t - \left(\frac{\text{min gradient}}{(\text{max } d)^2} \right)$ or For use of β from 2(e): $\Delta t = \left(\frac{\Delta \beta}{\beta} + \frac{\Delta z}{z} + \frac{\Delta(\rho - \sigma)}{(\rho - \sigma)} + \frac{2 \times 0.01}{1.20} \right) \times t \text{ or}$ $\Delta t = \left(\frac{18 \times \text{max } \beta \times \text{max } z}{g \times \text{min}(\rho - \sigma) \times (0.0120 - 0.0001)^2} \right) - t \text{ or}$ $\Delta t = t - \left(\frac{18 \times \text{min } \beta \times \text{min } z}{g \times \text{max}(\rho - \sigma) \times (0.0120 + 0.0001)^2} \right)$	1	Allow ecf from 2(c)(iii), 2(d) and 2(e)(i) and 2(e)(ii) for t $2\Delta d / d = 0.0167$ Allow clear method Note substitution needed Allow clear method Note substitution needed Note substitution needed